

HF DF Loop Antenna

VERSION: 1.0



ELECTRICAL FEATURES:

- HF DF
- 5-element interferometer

MECHANICAL FEATURES:

- Robust construction
- Naval hardened

RELATED PRODUCTS:

- DFS-A0313
- DF-A0314

1 – 30 MHz

Product Code: DF-A0313 SPECIFICATIONS:

Electrical:	
Frequency range	1 – 30 MHz
Nominal input impedance	50 Ω
Antenna type	5-element DF interferometer
Polarisation	Vertical
Output cables	RG 400 cables (qty 5)
Connectors	TNC male
Mechanical:	
Antenna weight	< 50 kg
Assembled height	< 1.3 m
Assembled diameter	< 2.6 m
Environmental: designed to meet the following specifications	
Maximum wind speed	150 km/h (without ice)

PRODUCT DESCRIPTION:

This direction finding antenna covers a frequency range of 1 MHz to 30 MHz. The antenna is hardened with supports to allow for Naval applications. The loops give excellent DF sensitivity in the HF band.

This DF antenna is designed to be used with a 5-channel phase-sensitive receiver, and correlative algorithm. Calibration of the antenna can be performed on request.

Updated 2022-02-15

sales@alaris.co.za www.alarisantennas.com

GAIN THE ADVANTAGE

PAGE 1 of 2

HF DF Loop Antenna


1 – 30 MHz

Product Code: DF-A0313

d Sonsitivity:

VERSION: 1.0

Estimated Sensitivity:



sales@alaris.co.za www.alarisantennas.com

Updated 2022-02-15

PAGE 2 of 2

Alaris Antennas has a policy of continuous improvement and hence specifications may change without notice

GAIN THE ADVANTAGE