

Manpack Wireless High-Power Antenna

850 – 2500 MHz

VERSION: 1.4

Product Code: OMNI-A0204

SPECIFICATIONS:



Electrical:	
Frequency range:	850 – 960 MHz
Band A	1700 – 2500 MHz
Band B	
Gain	3 – 4 dBi typical (in band)
Azimuth pattern	Omni, 3 dB ripple
Elevation pattern	Narrow beam
Polarisation	Vertical
Nominal input impedance	50 Ω
VSWR	< 2.5:1
Power handling	100W CW
Connector	N-type male at base
Groundplane requirements	Groundplane independent
Mechanical:	
Dimensions (l x d)	650 mm x 35 mm
Total mass	0.4 kg
Mounting	On N-type connector at base
Colour	Black, others on request
Environmental: designed to meet the following specifications	
Temperature range	Storage: -41 °C to +71 °C Operation: -31 °C to +55 °C
Weatherproofing	IP66 water resistant (when mounted on a connector)
Shock and vibration	MIL-STD-810E 516.4: vibration category 8, shock 40 g
Exposed materials	Painted fibreglass Powder-coated aluminium

PRODUCT FEATURES:

- High-gain communications
- High-power antenna
- Proven flexible base spring protects the antenna
- Covers all handheld wireless bands

APPLICATIONS:

- Intercepting of radio-controlled improvised explosive device (RCIED) signals
- Convoy protection

PRODUCT DESCRIPTION:

This banded antenna is for intercepting of wireless communications. It is mounted on an N-type male connector base, with a spring for shock absorption and flexibility. A glass-fibre tube contains the antenna RF board.

The array covers the GSM900, PCS, UMTS/3G and WLAN bands. Full specification coverage starts at 850 MHz, but there will be reduced performance down to 500 MHz. A 2-stack array of multi-band dipoles is used to provide gain at these frequencies, with a small down tilt to improve close-in coverage.

The lowest feed point is elevated about 500 mm from the base of the antenna, allowing the signal to be radiated over the user's head. This reduces absorbed power and increases field strength at the target.

Manpack Wireless High-Power Antenna

850 – 2500 MHz

Product Code: OMNI-A0204

VERSION: 1.3

GAIN:

VSWR:

