

Wideband UHF Manpack Antenna WB525G

The WB525G is a high performance manpack antenna that is particularly suited for applications where a quick adjustment of the antenna's angle is needed.

- Effective coverage of the complete 480 2800 MHz frequency range
- Flexible gooseneck for perfect operation, even in extreme positions



Product details*		
Frequency range	480 - 2800 MHz	
Matching	Passive	
Polarization	Nominally vertical	
Antenna type	Wideband dipole	
Radiation pattern	Omnidirectional	
Gain	Measured patterns on request	
VSWR	< 3.0	
Nominal Impedance	50 Ω	
Power rating	40 W (RMS)	
Standard color	Black	
Radiator	Radome protected	
Height	465 mm	
Weight	500 g (incl. 12 cm gooseneck)	

Installation*		
RF connection	Male N-type connector	
Mounting Directly to a matching connector		

^{*}Specific adjustments on request

Order number	NSN	Product
WB525G	5985 - 58 - 000 - 1015	Antenna as described above

Instructions for use: To avoid the connector from being damaged, do not rotate the antenna when the gooseneck is in a bent position. Always straighten the gooseneck first, before changing the bending direction.

The maximum bending angle of 60° shall not be exceeded.

V2.1w Date 22.05.2019

Page 1/1