

# High Power SBA for 4400-5000MHz

## SBA4450XB

The SBA4450XB is a high power switched beam antenna that is particularly suitable for tactical communication applications (UHF band IV). The antenna beam can be steered to achieve optimal gain to the desired direction and to avoid interference from unwanted directions (LPI/LPD). The antenna provides up to 20 sharp beams with a minimum of 20-degree beamwidth to cover the full 360-degree horizontal area. In addition to these sharp beams the antenna can also provide wider beams. Its extremely fast beam switching ability makes the antenna suitable for complex node network in tactical communication.

- Great directivity with very low side lobe levels to undesired direction (LPI/LPD)
- Fast beam switching by using RS-485/422 or Ethernet based communication
- High power rating – 100 W



Product details*	
Frequency range	4400 - 5000 MHz
Polarization	Nominally vertical
Antenna type	Switched beam antenna
Radiation pattern	Directional and omni (sharp, wide and omni beams)
Gain (typical)	14 dBi
3 dB beamwidth (typical)	25° (H-plane), 15° (H-plane)
Sidelobe level (typical)	-14 dB
VSWR	≤ 2.0
Nominal Impedance	50 Ω
Power rating	100 W (CW)
Power supply	19 – 32 VDC (<200 mA), MIL-STD-1275E
Beam switching speed	< 1 μs (see information on Page 3)
Standard color	Black
Radiator	Selectable patch array element, 20 elements
Height	390 mm (including the mast mount adapter)
Diameter	290 mm
Weight	4.5 kg

Installation*	
RF connection	Female N-type connector
Power and control	See information on Page 3
Mounting	Mast mount adapter for 40-60 mm masts included **

\* More information on request

\*\* Vehicle mounting option available

Order number	
SBA4450XB	Antenna as described above