



1427 - 1535 MHz Compak Grid

Designed to deliver performance for decades

Features

- Lightweight and durable construction.
- · Feed input Type N as shown, others noted below.
- Parabolic Grid designs typically offer 40% lower wind-loading, when compared to a like sized solid antenna without ice.
- · Feed guy supports are included when necessary.
- Antenna features independent azimuth and elevation adjustment.
- Antenna Survival Ratings: 1 inch (25mm) of ice and 125 mph (201 kmh) wind.
- Universal (U) mounts mate to 1.9 in. 4.5 in. O.D.
 (48 mm 114 mm) vertical pipe mast.
 Available on 4-ft. 6-ft. (1.2-m 1.8-m)
- All mWAVE Mark Grid Series antennas meet or exceed Standard ANSI/TIA-222.



The mWAVE Mark Compak grid reflectors ship in 4 pieces for ease of handeling on site and shipping. The antennas have the same performance as their single piece counterparts.



Electrical Specifications

Frequency	Model No.	Size Pol.			Pog	Gain, nominal dBi			HPBW	XPD	F/B	VSWR	R.L.
MHz		POI.	ft.	m.	Reg.	Low	Mid	High	Deg.	dB	dB	max	dB
1427 – 1535	P-15A48KGN-U	LP	4	1.2	n/a	23.3	23.7	24.0	10.4	30	31	1.3:1	17.7
1427 – 1535	P-15A72KGN-U	LP	6	1.8	n/a	27.2	27.5	27.8	7.0	30	36	1.3:1	17.7
1427 – 1535	P-15A96KGN-S	LP	8	2.4	n/a	29.2	29.5	29.8	5.3	30	36	1.3:1	17.7

Notes:

* Optional input connectors available.

F = 7/8 EIA Flange Non-pressurized

P = 7/8 EIA Air Dielectric Non-pressurized

L = 7/8 EIA Flange Pressurized Low VSWR N = N-Female Connector Non-Pressurized

E = 7/16 DIN Connector Non-Pressurized

** Compliance: U.S.F.C.C. Part 101.115

Contact mWAVE for other regulatory compliance.

*** 10-ft (3.0), 12-ft (3.7) and 15-ft (4.6) parabolic grids ship in two halves.

**** 8-ft (2.4) model is available as a split reflector (X2) on request.

Product information is subject to change without notice.



Designed, Engineered, and Manufactured in Windham, ME USA mWAVE Industries is part of the Alaris Holdings Group of Companies.

© mWAVE Industries LLC - 2022 All rights reserved

Form: 1427-1535-Compak Grid-221123.R2

