

Model Series

RFFx-940-N

940 - 960 MHz Standard Solid Parabolic

Designed to perform

Features

- Gabriel Quality and Dependability.
- Standard Feed input is a Type "N" Female, 50 ohm.
(other types available on request, see below.)
- Feeds may be installed from the front or rear of the antenna.
- Solid Reflector models offer polarization change from the rear of the antenna.
- Feed guy supports are included when necessary.
- Antenna features independent azimuth and elevation adjustments.
- Antenna Survival Ratings: 1 inch (25mm) of ice and 125 mph (201 kmh) wind.
- Antenna mounts to 4.5 in. OD (114 mm) (4 in. IPS) vertical pipe mast. Optional 2.38 in. - 4 in. OD (60 mm - 102 mm) mast mount available for 4 ft (1.2 m) antenna.
- Elevation adjustment range for 4 ft. (1.2 m) and 6 ft. (1.8 m) antennas is +50° to - 5°; invert the mount for -50° and +5°.
- Elevation adjustment range for 8 ft. (2.4 m) antennas is +/-7.5°.
- All mWAVE – Gabriel – Mark antennas meet or exceed Standard ANSI/TIA-222.



All antennas in this product line are available with optional radomes, wind brace struts and optional input connectors. mWAVE's Gabriel production color is gray with aviation white, aviation orange and custom colors available.

This product line is configurable for Severe Environment conditions.

Electrical Specifications

Frequency MHz	Model No.	Pol.	Size		Reg.	Gain, nominal dBi			HPBW Deg.	XPD dB	F/B dB	VSWR max	R.L. dB
			ft.	m.		Low	Mid	High					
940 – 960	RFF4-940A-N	LP	4	1.2	B**	18.6	18.7	18.8	18.2	26	24	1.3:1	17.7 †
940 – 960	RFF6-940A-N	LP	6	1.8	A**	22.0	22.1	22.2	12.0	28	26	1.3:1	17.7 †
940 – 960	RFF8-940B-N	LP	8	2.4	A**	24.5	24.6	24.7	9.0	29	28	1.3:1	17.7 †

Notes:

- (1.) Referenced product specifications are subject to change without notice.
- (2.) Designed, Engineered, and Manufactured in Windham, ME USA
- (3.) mWAVE Industries is part of the Alaris Holdings Group of Companies.
- (4.) © mWAVE Industries LLC - 2022 All rights reserved.

- Notes:
- * Optional input connectors available.
 - F = 7/8 EIA Flange Non-pressurized
 - N = N-Female Connector Non-Pressurized
 - E = 7/16 DIN Connector Non-Pressurized
 - ** Compliance: U.S.F.C.C. Part 101.115
Contact mWAVE for other regulatory compliance.
 - *** 10-ft (3.0), 12-ft (3.7) and 15-ft (4.6) parabolic grids ship in two halves.
 - **** 8-ft (2.4) model is available as a split reflector (X2) on request.

Form: 940-960 MHz Standard Parabolic Line-220329_rev.1-DS

