

## Parabolic Grids 1427 - 1535 MHz



## 1427 - 1535 MHz Parabolic Grid

Designed to deliver performance for decades

## Features

- Lightweight and durable construction.
- Feed input Type N as shown, others noted below.
- Parabolic Grid designs typically offer 40% lower wind-loading, when compared to a like sized solid antenna without ice.
- Feed guy supports are included when necessary.
- Antenna features independent azimuth and elevation adjustment.
- Antenna Survival Ratings: 1 inch (25mm) of ice and 125 mph (201 kmh) wind.

Antenna Mount Types: **Standard (S) mounts** mate to a 4.5 in. O.D. (114 mm) (4 in. IPS) vertical pipe mast. Available on 6-ft. – 15-ft. (1.8-m – 4.6-m) **Universal (U) mounts** mate to 1.9 in.– 4.5 in. O.D. (48 mm – 114 mm) vertical pipe mast. Available on 4-ft. – 6-ft. (1.2-m – 1.8-m) All mWAV/F – Mark Crid Spring antennas most or evened

 All mWAVE – Mark Grid Series antennas meet or exceed Standard ANSI/TIA-222.

mWAVE supports all current and legacy Mark parabolic grids with feeds, wind brace kits and other miscellaneous parts and tuning services.

Frequency	Model No.	Del	S	Size		Gain, nominal dBi			HPBW XPD	F/B	VSWR	R.L.	
MHz		Pol.	ft.	m.	Reg.	Low	Mid	High	Deg.	dB	dB	max	dB
1427 – 1535	P-15A36GN-U	LP	3	0.9	n/a	20.8	21.1	21.4	13.5	34	26	1.5:1	14.0
1427 – 1535	P-15A48GN-U	LP	4	1.2	n/a	23.8	23.7	24.0	10.0	31	31	1.3:1	17.7
1427 – 1535	P-15A72GN-U	LP	6	1.8	n/a	27.2	27.5	27.8	7.0	34	36	1.3:1	17.7
1427 – 1535	P-15A72GN-S	LP	6	1.8	n/a	27.2	27.5	27.8	7.0	34	36	1.3:1	17.7
1427 – 1535	P-15A96GN-S	LP	8	2.4	n/a	29.2	29.5	29.8	5.3	36	36	1.3:1	17.7
1427 – 1535	P-15A120GN-S	LP	10	3.0	n/a	30.4	30.7	31.1	4.5	35	38	1.3:1	17.7
1427 – 1535	P-15A144GN-S	LP	12	3.7	n/a	32.7	33.0	33.3	3.6	41	41	1.3:1	17.7
1427 – 1535	P-15A188GN-2	LP	15	4.6	n/a	34.2	34.5	34.8	2.9	45	41	1.3:1	17.7

Notes: \* Optional input connectors available.

**Electrical Specifications** 

F = 7/8 EIA Flange Non-pressurized

P = 7/8 EIA Air Dielectric Non-pressurized

L = 7/8 EIA Flange Pressurized Low VSWR

N = N-Female Connector Non-Pressurized

E = 7/16 DIN Connector Non-Pressurized

\*\* Compliance: U.S.F.C.C. Part 101.115

Contact mWAVE for other regulatory compliance.

\*\*\* 10-ft (3.0), 12-ft (3.7) and 15-ft (4.6) parabolic grids ship in two halves.

\*\*\*\* 8-ft (2.4) model is available as a split reflector (X2) on request.

Product information is subject to change without notice.

 Designed, Engineered, and Manufactured in Windham, ME USA mWAVE Industries is part of the Alaris Holdings Group of Companies.
mWAVE Industries LLC - 2022 All rights reserved

Form: 1427 - 1535-Grid-221123.R2-DS



*mWAVE* Industries LLC 33R Main Street Windham, ME 04062 - USA Your partner in antenna technology

info@mwavellc.com www.mwavellc.com

207.892.0011