

## Parabolic Grids 350 - 380 MHz



## 350 - 380 MHz Parabolic Grid

Designed to deliver performance for decades

## Features

- Lightweight and durable construction.
- Feed input Type N as shown, others noted below.
- Parabolic Grid designs typically offer 40% lower wind-loading, when compared to a like sized solid antenna without ice.
- Feed guy supports are included when necessary.
- Antenna features independent azimuth and elevation adjustment.
- Antenna Survival Ratings: 1 inch (25mm) of ice and 125 mph (201 kmh) wind.

Antenna Mount Types: **Standard (S) mounts** mate to a 4.5 in. O.D. (114 mm) (4 in. IPS) vertical pipe mast. Available on 6-ft. – 15-ft. (1.8-m – 4.6-m) **Universal (U) mounts** mate to 1.9 in.– 4.5 in. O.D. (48 mm – 114 mm) vertical pipe mast. Available on 4-ft. – 6-ft. (1.2-m – 1.8-m) All mWAVE – Mark Crid Spring aptendage most or exceed

 All mWAVE – Mark Grid Series antennas meet or exceed Standard ANSI/TIA-222.

## **Electrical Specifications**



mWAVE supports all current and legacy Mark parabolic grids with feeds, wind brace kits and other miscellaneous parts and tuning services.

Frequency	Model No.	Del	Size		Dee	Gain, nominal dBi			HPBW	XPD	F/B	VSWR	R.L.
MHz		Pol.	ft.	m.	Reg.	Low	Mid	High	Deg.	dB	dB	max	dB
350 – 380	P-3A48GN-U	LP	4	1.2	n/a	10.2	10.5	10.7	44.5	11	18	1.5:1	14.0
350 – 380	P-3A72GN-U	LP	6	1.8	n/a	13.9	14.2	14.6	28.0	19	22	1.3:1	17.7
350 – 380	P-3A72GN-S	LP	6	1.8	n/a	13.9	14.2	14.6	28.0	19	22	1.3:1	17.7
350 – 380	P-3A96GN-S	LP	8	2.4	n/a	16.4	16.7	17.4	21.5	18	24	1.3:1	17.7
350 – 380	P-3A120GN-S	LP	10	3.0	n/a	18.1	18.5	18.9	19.0	20	22	1.3:1	17.7
350 – 380	P-3A144GN-S	LP	12	3.7	n/a	19.4	19.6	20.0	17.0	20	24	1.3:1	17.7

Notes: \* Optional input connectors available.

F = 7/8 EIA Flange Non-pressurized

P = 7/8 EIA Air Dielectric Non-pressurized

L = 7/8 EIA Flange Pressurized Low VSWR

N = N-Female Connector Non-Pressurized

E = 7/16 DIN Connector Non-Pressurized

Contact mWAVE for other regulatory compliance.

\*\*\* 10-ft (3.0), 12-ft (3.7) and 15-ft (4.6) parabolic grids ship in two halves.

\*\*\*\* 8-ft (2.4) model is available as a split reflector (X2) on request.

Designed, Engineered, and Manufactured in Windham, ME USA mWAVE Industries is part of the Alaris Holdings Group of Companies. © mWAVE Industries LLC - 2022 All rights reserved

Form: 350-380-Grid-221031.R1 DS

*mWAVE* Industries LLC 33R Main Street Windham, ME 04062 - USA Your partner in antenna technology

info@mwavellc.com

207.892.0011

www.mwavellc.com