



470 - 608 MHz Parabolic Grid

Designed to deliver performance for decades

Features

- Lightweight and durable construction.
- Feed input Type N as shown, others noted below.
- Parabolic Grid designs typically offer 40% lower wind-loading, when compared to a like sized solid antenna without ice.
- Feed guy supports are included when necessary.
- Antenna features independent azimuth and elevation adjustment.
- Antenna Survival Ratings: 1 inch (25mm) of ice and 125 mph (201 kmh) wind.
- Antenna Mount Types:

Standard (S) mounts mate to a 4.5 in. O.D. (114 mm) (4 in. IPS) vertical pipe mast. Available on 6-ft. - 15-ft. (1.8-m - 4.6-m)

Universal (U) mounts mate to 1.9 in. - 4.5 in. O.D.

(48 mm - 114 mm) vertical pipe mast.

Available on 4-ft. – 6-ft. (1.2-m – 1.8-m)

All mWAVE - Mark Grid Series antennas meet or exceed Standard ANSI/TIA-222.



mWAVE supports all current and legacy Mark parabolic grids with feeds, wind brace kits and other miscellaneous parts and tuning services.

Electrical Specifications

| Frequency | Model No. | Size | | | | Gain, nominal dBi | | | HPBW | XPD | F/B | VSWR | R.L. |
|-----------|--------------|------|-----|-----|------|-------------------|------|------|------|-----|-----|-------|------|
| MHz | | Pol. | ft. | m. | Reg. | Low | Mid | High | Deg. | dB | dB | max | dB |
| 470 – 608 | P-6LA48GN-U | SP | 4 | 1.2 | n/a | 13.3 | 14.5 | 15.6 | 31.3 | 25 | 18 | 1.5:1 | 14.0 |
| 470 – 608 | P-6LA72GN-U | SP | 6 | 1.8 | n/a | 16.9 | 18.1 | 19.1 | 20.8 | 28 | 25 | 1.3:1 | 17.7 |
| 470 – 608 | P-6LA72GN-S | SP | 6 | 1.8 | n/a | 16.9 | 18.1 | 19.1 | 20.8 | 28 | 25 | 1.3:1 | 17.7 |
| 470 – 608 | P-6LA96GN-S | SP | 8 | 2.4 | n/a | 19.4 | 20.6 | 21.6 | 15.6 | 30 | 26 | 1.3:1 | 17.7 |
| 470 – 608 | P-6LA120GN-S | SP | 10 | 3.0 | n/a | 21.3 | 22.5 | 23.5 | 11.1 | 30 | 30 | 1.3:1 | 17.7 |
| 470 – 608 | P-6LA144GN-S | SP | 12 | 3.7 | n/a | 22.9 | 24.1 | 25.1 | 9.2 | 30 | 30 | 1.3:1 | 17.7 |

Notes:

* Optional input connectors available.

F = 7/8 EIA Flange Non-pressurized

P = 7/8 EIA Air Dielectric Non-pressurized

L = 7/8 EIA Flange Pressurized Low VSWR N = N-Female Connector Non-Pressurized

E = 7/16 DIN Connector Non-Pressurized

Contact mWAVE for other regulatory compliance.

**** 8-ft (2.4) model is available as a split reflector (X2) on request.

Designed, Engineered, and Manufactured in Windham, ME USA mWAVE Industries is part of the Alaris Holdings Group of Companies. © mWAVE Industries LLC - 2022 All rights reserved

Form: 470-608-Grid-220718.R2 DS

